



| MODEL | Capacity in kg. | FEM duty | ISO duty | Lifting speed mpm | | Chain Diameter in mm | No. of falls | Motor kw main/creep | Motor RPM | 'A' Headroom | | B | C | E | G | H | L | Wt.(kg) Hook susp. 3m lift | Wt.(k with ET 3m li | | | | | | |
|------------|-----------------|----------|----------|-------------------|-------|----------------------|--------------|---------------------|-----------|--------------|---------|---------|----------|---------|----------|-----|-----|----------------------------|---------------------|-----|----|-----|-----|-----|-----|
| | | | | Single | Dual | | | | | HOOK SUSP. | TROLLEY | | | | | | | | | | | | | | |
| HC1+ 025NL | 250 | 3M | M6 | 4 | | 4 | ONE | 0.25 | 1500 | 550 | 560 | 200 | 200 | 280 | 32 | 300 | 250 | 30 | 65 | | | | | | |
| HC1+ 025DL | | | | | 4/1.3 | | ONE | 0.25/0.08 | 1500/500 | 550 | 560 | | | 280 | 32 | 300 | 250 | 35 | 70 | | | | | | |
| HC2+ 025NH | | | | | 8 | | ONE | 0.55 | 1500 | 550 | 560 | | | 280 | 32 | 300 | 250 | 40 | 75 | | | | | | |
| HC2+ 025DH | | | | | 8/2.6 | | ONE | 0.55/0.18 | 1500/500 | 550 | 560 | | | 280 | 32 | 300 | 250 | 45 | 80 | | | | | | |
| HC2+ 050NL | 500 | 2M | M5 | 4 | | 6 | ONE | 0.55 | 1500 | 550 | 560 | 200 | 200 | 280 | 32 | 300 | 250 | 40 | 75 | | | | | | |
| HC2+ 050DL | | | | | 4/1.3 | | ONE | 0.55/0.18 | 1500/500 | 550 | 560 | | | 280 | 32 | 300 | 250 | 40 | 80 | | | | | | |
| HC3+ 050NH | | | | | 8 | | ONE | 0.9 | 1500 | 550 | 560 | | | 280 | 32 | 300 | 250 | 55 | 90 | | | | | | |
| HC3+ 050DH | | | | | 8/2.6 | | ONE | 0.85/0.3 | 1500/500 | 550 | 560 | | | 280 | 32 | 300 | 250 | 60 | 95 | | | | | | |
| HC3+ 100NL | 1000 | 2M | M5 | 4 | | 7 | ONE | 0.9 | 1500 | 550 | 560 | 200 | 200 | 280 | 32 | 300 | 250 | 55 | 90 | | | | | | |
| HC3+ 100DL | | | | | 4/1.3 | | ONE | 0.85/0.3 | 1500/500 | 550 | 560 | | | 280 | 32 | 300 | 250 | 60 | 95 | | | | | | |
| HC4+ 100NH | | | | | 8 | | ONE | 1.84 | 1500 | 600 | 625 | | | 350 | 32 | 450 | 380 | 90 | 125 | | | | | | |
| HC4+ 100DH | | | | | 8/2.6 | | ONE | 1.7/0.6 | 1500/500 | 600 | 625 | | | 350 | 32 | 500 | 380 | 100 | 140 | | | | | | |
| HC4+ 200NL | 2000 | 2M | M5 | 4 | | 10 | ONE | 1.84 | 1500 | 600 | 625 | 280 | 325 | 350 | 38 | 450 | 380 | 90 | 135 | | | | | | |
| HC4+ 200DL | | | | | 4/1.3 | | ONE | 1.7/0.6 | 1500/500 | 600 | 625 | | | 350 | 38 | 500 | 380 | 100 | 150 | | | | | | |
| HC4+ 200NH | | | | | 8 | | ONE | 3.5 | 1500 | 600 | 625 | | | 350 | 38 | 500 | 380 | 100 | 150 | | | | | | |
| HC4+ 200DH | | | | | 8/2.6 | | ONE | 3.5/1.2 | 1500/500 | 600 | 625 | | | 350 | 38 | 500 | 380 | 100 | 150 | | | | | | |
| HC4+ 250NL | 2500 | 2M | M5 | 4 | | 10 | ONE | 2.2 | 1500 | 600 | 625 | 280 | 325 | 350 | 38 | 450 | 380 | 90 | 150 | | | | | | |
| HC4+ 250DL | | | | | 4/1.3 | | ONE | 2.5/0.8 | 1500/500 | 600 | 625 | | | 350 | 38 | 600 | 380 | 110 | 170 | | | | | | |
| HC5+ 300NL | | | | 3000 | 2M | | M5 | 4 | | 10 | TWO | | | 3.5 | 1500 | 950 | 870 | 280 | 325 | 350 | 46 | 500 | 400 | 125 | 185 |
| HC5+ 300DL | | | | | | | | | 4/1.3 | | TWO | | | 3.5/1.2 | 1500/500 | 950 | 870 | | | 350 | 46 | 600 | 400 | 160 | 200 |
| HC6+ 500NL | 5000 | 2M | M5 | | | 4 | | | 10 | | TWO | 4.5 | 1500 | 1000 | 1100 | 280 | 325 | | | 800 | 53 | 500 | 400 | 170 | 250 |
| HC6+ 500DL | | | | | | | | 4/1.3 | | | TWO | 4.5/1.5 | 1500/500 | 1000 | 1100 | | | | | 800 | 53 | 600 | 400 | 200 | 280 |

NOTE : Specification/Dimensions (mm)

Data tolerance $\pm 10\%$

All dimensions are in mm Tolerance $\pm 10\%$

* Key abbreviations used in models are :

H- High Hoisting speed(8 & above) N- Single speed (Normal speed)

L- Low Hoisting speed (4 & below) D- Dual speed

* All Dimensions in mm. Data is subjected to change without prior notice.

* Standard chain collector upto 6.0m lift (2 Fall). 12m lift Single fall only.